



## PART NUMBER: 6U-CHAS-2222U

- In accordance with IEC 60297-3-101, -102, -103; IEEE 1101.1, 1101.10/11; backplane in accordance with PICMG 2.0 rev. 3.0
- Horizontal card cage
- Backplane (signal and power backplane in one unit) 8 slot, 4U, 64 bit
- Heat dissipation by hot-swap fan unit
- Prepared for the assembly of a 19" power supply

## SPECIFICATION

### Summary

- Product Type: System
- Number of Slots: 8
- Type: 19" Rack Mount
- Backplane Type: 6 U CompactPCI
- Data Transfer: 64-bit PCI Bus
- Power per Slot: 40 W
- Input Voltage AC: 100 – 240 V
- Airflow Direction: Left to Right
- Rack Height: 4 U
- Power Supply Type: (2) Pluggable PSU
- Power Supply Included: No
- Rear I/O: Yes
- Complies With: PICMG 2.0 R3.0
- Depth: 275 mm
- Height: 177 mm
- Width: 449 mm

## The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

- 📍 Unit 13 Suttons Business Park, Reading, RG6 1AZ
- ☎ 0118 929 4990
- ✉ [uk.sales@hiper-global.com](mailto:uk.sales@hiper-global.com)
- 🌐 [www.hiper-global.co.uk](http://www.hiper-global.co.uk)