



PART NUMBER: 6U-PER-IOMODULE

- External rear-panel interface connector for CPU board
- Supports SATA, USB 2.0, COM, VGA and PS/2 interfaces
- Two PICMG 2.16 LAN ports on the rear panel

SPECIFICATION

CompactPCI Connector	J3 /J5		
Front I/O	USB2.0	2 type A	
	COM	Up to 2 RS232/422/485 on RJ45 & D-Sub	
	LAN	Up to 4 10/100/1000Mbps on RJ45	
	Graphics	1 VGA	
	PS/2	PS/2 (KB/Mouse)	
Physical	Dimensions	233.35 x 80 mm (9.2" x 3.15"), Single slot width	
	Weight	0.3 kg (0.66lbs)	
Environmental		Operating	Non-Operating
	Temperature	0 ~ 60° C (32 ~ 140° F)	-40 ~ 85° C (-40 ~ 185° F)
	Humidity	95 % @ 40° C, non-condensing	95 % @ 60° C, non-condensing

The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

-  Unit 13 Suttons Business Park, Reading, RG6 1AZ
-  0118 929 4990
-  uk.sales@hiper-global.com
-  www.hiper-global.co.uk

The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

-  Unit 13 Suttons Business Park, Reading, RG6 1AZ
-  0118 929 4990
-  uk.sales@hiper-global.com
-  www.hiper-global.co.uk

