



## PART NUMBER: IPC-CHASSIS

- Compact IPC chassis with two/four front expansion slots
- Shockproof drive bay for two 2.5" HDD/SSD
- Single-side I/O for easy maintenance
- Support for expansion modules
- Bi-directional to mount on wall or workbench
- Qualified for AWS (Amazon Web Service) IoT Greengrass

## SPECIFICATION

<b>Disk Drive Bay</b>	2.5"	2 Swappable (Max height 15mm)	
<b>Cooling</b>	Fan / Air Filters	1 (12cm/82CFM) / Yes	
<b>Front I/O</b>	USB	8	
	LAN	2	
	Video Output	HDMI, VGA	
	Audio	Mic-in, Line-out	
	Serial Port	2 x RS-232/422/485 support auto flow control	
	Remote SW	Used for remote power on/off signal	
	DC Outlet	12V@2A max; 5V@2A max	
<b>Expansion</b>	Contact HIPER Global at <a href="mailto:uk.sales@hiper-global.com">uk.sales@hiper-global.com</a> or via 0118 929 4990 to find out more		
<b>Miscellaneous</b>	Control	Power switch	
	LED Indicator	Power / Disk / CPU Temp. Alarm / System Temp. Alarm / CPU Fan Alarm / Watch Dog	
<b>Environment</b>		Operating	Non-operating
	Temperature	0 ~ 45 °C	-40 ~ 85 °C
	Humidity	95% @ 40 °C (non-condensing)	
	Vibration (5~500 Hz)	With SSD: 2 Grms @ 5 ~ 500 Hz, random, 1 hr/axis	
		With HDD: 0.5Grms @ 5 ~ 500 Hz, random, 1 hr/axis	
Shock	10G, IEC-68-2-27, half-sine wave, 11 ms duration		
<b>Mechanical</b>	Dimensions (WxHxD)	2-slot: 155 x 230 x 150 mm (6.1" x 9.05" x 5.9")	
		4-slot: 195 x 230 x 150 mm (7.68" x 9.05" x 5.9")	
	Weight	2-slot: 3.1 kg	
		4-slot: 3.3 kg	

## The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

-  Unit 13 Suttons Business Park, Reading, RG6 1AZ
-  0118 929 4990
-  [uk.sales@hiper-global.com](mailto:uk.sales@hiper-global.com)
-  [www.hiper-global.co.uk](http://www.hiper-global.co.uk)