

## Global CompactPCI® SSD Carrier

mSATA SSD RAID CARD



## **PART NUMBER: 3U-PER-MSATA**

A peripheral slot card for CompactPCI<sup>®</sup> serial systems, equipped with a quad-channel PCI Express<sup>®</sup> to SATA 6Gbps controller and four onboard sockets for mSATA solid state drives (SSD). With a capacity available of up to 1TB as of current, mSATA is a popular embedded storage module form factor. The Marvell<sup>®</sup> SATA 3.0 controller allows RAID or non RAID operation.

## SPECIFICATION

Summary	<ul> <li>PICMG® CompactPCI® Serial standard (CPCI-S.0)</li> <li>Single size Eurocard 3U 4HP 100x160mm2</li> <li>Suitable for CompactPCI® Serial peripheral slot (PCI Express® enabled)</li> <li>CompactPCI® Serial fat pipe slot (PCI e x 8) or peripheral slot (PCI e x 4) recommended</li> <li>CompactPCI® Serial backplane connector P1 for PCI Express®, single or dual lane link</li> <li>Marvell® PCI Express® 2.0 to SATA III host controller</li> <li>Four SATA 6Gbps interface ports (backward support 3Gbps and 1.5Gbps)</li> <li>Native Command Queuing</li> <li>Hardware RAID 0/1/10</li> <li>On-the-fly AES encryption 128/256-bit</li> <li>AHCI driver support</li> <li>Up to four on-board mSATA SSD modules (must be ordered separately)</li> <li>Half or full size accepted</li> <li>Various brands of mSATA SSD available (e.g. Intel, Micron, Samsung)</li> <li>Hardware RAID option for dual or triple/quad device configuration</li> </ul>
	<ul> <li>Designed &amp; manufactured in Germany</li> <li>ISO 9001 certified quality management system</li> <li>Long term availability</li> <li>Rugged solution (coating, sealing, underfilling on request)</li> <li>RoHS compliant</li> <li>Operation temperature 0°C to +70°C (commercial temperature range)</li> <li>Operation temperature -40°C to +85°C (industrial temperature range) on request</li> <li>Storage temperature -40°C to +85°C</li> <li>Humidity 5% 95% RH non condensing</li> <li>Altitude -3000 +3000m</li> <li>Shock 15g 0.33ms, 6g 6ms</li> <li>Vibration 1g 5-2000Hz</li> <li>MTBF 82.8 years</li> <li>EC Regulations EN55022, EN55024, EN60950-1 (UL60950-1/IEC60950-1)</li> </ul>

## The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

- Unit 13 Suttons Business Park, Reading, RG6 1AZ
- **(**) 0118 929 4990
- uk.sales@hiper-global.com
- www.hiper-global.co.uk