



PART NUMBER: RM-CAB-10U

- System designed in accordance with: MIL-STD-810F, MIL-STD-167, MIL-STD-461, IP 20
- For rugged applications with increased shock and vibration resistance
- Backplane VPX 10 slot, 6U
- 100 to 240 VAC input on the back
- 6U front card cage and 6U Rear I/O card cage with 10 slot VPX backplane
- Prepared for telescopic slides

SPECIFICATION

Summary

- Product Type: System
- Number of Slots: 10
- Type: Rugged 19" Rack Mount
- Backplane Type: VPX, VITA 65
- Data Transfer: 10 GbE; PCIe Gen3
- Power per Slot: 50 W
- Input Voltage AC: 100 – 240 V
- Airflow Direction: Front to Rear
- Rack Height: 10 U
- Power Supply Type: (1) Pluggable PSU
- Power Supply Included: Yes
- Rear I/O: Yes
- Complies With: ANSI/VITA 46.0-2019
- Power: 1000 W
- Depth: 490 mm
- Height: 443.7 mm
- Width: 480 mm

The Power to Outperform

Would you like to find out more? Be sure to speak to our on-stand team or contact us via the details here and we would be happy to help.

- 📍 Unit 13 Suttons Business Park, Reading, RG6 1AZ
- ☎ 0118 929 4990
- ✉ uk.sales@hiper-global.com
- 🌐 www.hiper-global.co.uk